






# ButtKicker/Pearl Product Comparison Chart for Pro Audio and MI

		For Drummers & other Seated Musicians or Studio Engineers			Bass Players & other Standing Musicians	
						
<b>PRODUCT</b>		<b>ButtKicker Drum Throne Rig</b>	<b>Pearl Throne Thumper by ButtKicker</b>	<b>ButtKicker Gamer</b>	<b>ButtKicker Standing Platform Kit</b>	<b>Large Platform and Stage Installations</b>
<b>IDEAL FOR</b>		Thrones and other seats – Heavy duty	Thrones and single-post seats – Medium duty	Thrones and single-post seats – Light duty	Bass players and other standing musicians	Large platforms/stages and multiple units
<b>Transducer Specifications</b>	<b>TRANSDUCER TYPE</b>	ButtKicker Concert	ButtKicker Advance Series	ButtKicker mini Series	ButtKicker Concert	ButtKicker LFE (multiple units as needed)
	<b>INTERNAL PISTON MASS</b>	3.25 lbs.	1 lbs.	6 oz.	3.25 lbs.	3.25 lbs.
	<b>DIMENSIONS</b>	5.375" H x 5.375" W	4.375" H	11.5" L x 2.75" H x 3" W	5.375" H x 5.375" W	5.5"
	<b>FREQUENCY RESPONSE</b>	5 – 200 Hz	10 - 250 Hz	10 – 250 Hz	Currently Discontinued	5 – 200 Hz
	<b>TOTAL WEIGHT</b>	11 lbs. / 5 kgs.	Approx. 5 lbs.	3 lbs. / 1.3 kgs.		11 lbs. / 5 kgs.
	<b>NOMINAL IMPEDANCE</b>	2 ohms	4 ohms	2 ohms	2 ohms	4 ohms
	<b>POWER HANDLING</b>	400 watts min. / 1500 watts max.	75 watt min. / 400 wats max.	75 watt min. / 400 watt max.	400 watts min. / 1500 watts max.	400 watts min. / 1500 watts max.
	<b>MOUNTING OPTIONS</b>	Screw or DTM Mounting Plate	Easy-Clamp™	Easy-Clamp™	Screw/Bolt	Screw/Bolt

... Continued from page 1

PRODUCT	ButtKicker Drum Throne Rig	Pearl Throne Thumper by ButtKicker	ButtKicker Gamer	ButtKicker Standing Platform Kit	Large Platform and Stage Installations	
<b>Amplifier Specifications</b>	<b>AMPLIFIER WATTAGE</b>	1900 Watts @ 2 ohms 1000 Watts @ 4 ohms	200 Watts @ 4 ohms (2 ohms Not Recommended)	90 Watts @ 2 ohms 45 Watts @ 4 ohms	1900 Watts @ 2 ohms 1000 Watts @ 4 ohms	1900 Watts @ 2 ohms 1000 Watts @ 4 ohms
	<b>HIGH FILTER CUTOFF</b>	Variable, 40 – 160 Hz	N/A	Variable, 40 – 160 Hz	Variable, 40 – 160 Hz	Variable, 40 – 160 Hz
	<b>LOW FILTER CUTOFF</b>	25 Hz (switchable)	N/A	25 Hz (switchable)	25 Hz (switchable)	25 Hz (switchable)
	<b>INPUT</b>	RCA and 1/4" inputs with 160 mVolt and 1.25 Volt sensitivities	1/4" input with 100 mVolt Sensitivity	RCA input with 75 mVolt sensitivity	RCA and 1/4" inputs with 160 mVolt and 1.25 Volt sensitivities	RCA and 1/4" inputs with 160 mVolt and 1.25 Volt sensitivities
	<b>OUTPUT</b>	5-way Binding Post	5-way Binding Post	5-way Binding Post	5-way Binding Post	5-way Binding Post
	<b>POWER COMPATIBILITY</b>	Either 120v or 240v versions. NOT SWITCHABLE	Either 120v or 240v versions. NOT SWITCHABLE	Either 120v or 240v versions. NOT SWITCHABLE	Currently Discontinued	Either 120v or 240v versions. NOT SWITCHABLE
	<b>COOLING</b>	Convection Cooled	Convection Cooled	Convection Cooled	Convection Cooled	Convection Cooled
<b>MSRP</b>	\$669.99	\$499.99	\$149.95	\$649.85	Varies by product configuration	
<b>MAP</b>	\$539.99	\$299.99	\$129.99	\$529.99	Varies by product configuration	
<b>AVAILABLE THROUGH</b>	Guitammer	Pearl	Guitammer	Guitammer	Guitammer	